Aktuelle Daten für den Tag: 08-05-2024 14:44

Link zum Produkt:
https://treppenbeleuchtung.info/ls2-wp-5-in-1-intelligentem-led-steuerung-rgb-cct-rgbw-rgb-cct-mono-p-2659.html

LS2-WP 5 in 1 intelligentem LED Steuerung RGB + CCT / RGBW / RGB / CCT / MONO

Preis	**62.40 Euro**
Verfügbarkeit	**Verwendbarkeit - 3 Tage**
Versanddauer	**14 Tage**
Katalognummer	**2659**
Erzeuger	**Mi.Light**

Produktbeschreibung

Produktname: Wasserdichter 5-in-1-LED-Controller
Modell Nr.: LS2-WP
Eingangsspannung: DC12V~36V
Ausgang: 6A/Kanal
Gesamtleistung max.: 20A
Anschluss: Gemeinsame Anode
HF: 2,4 GHz
Reichweite der Fernbedienung: 30 m
Arbeitstemperatur: -20 ~ 45 ℃
IP-Rate: IP67

Waterproof 5-in-1 LED Controller
2.4GHz remote control | Support third-party voice control
With anti-reverse short circuit protection
DC12V~36V wide voltage
16 million colors
Color temperature
Dimmable
Saturation
Signal transmitting&
Modes synchronization
IP67
IP Rate


31mm
180mm
185mm
180mm


136mm
V+
V–
87mm


5 output mode selection
SET key switch mode
Brightness mode
Color temperature mode
RGB mode
RGBW mode
RBG+CCT mode
SET

IP67 waterproof rating
Waterproof design, eliminates potential safety hazards and makes use safer


16 million colors | Saturation adjustment
Easily create the lighting atmosphere you want to meet the needs of different scenarios
Brightness adjustment
Adjust the brightness of the LED light through the remote control
IP67

Adjust warm white to cool white randomly

Adjust the color temperature from 2700K-6500K, make the light you want



Signal transmitting

One controller can transmit the signals from the remote control to another controller within 30m, as long as there is a controller within 30m, the remote control distance can be limitless.

Modes synchronization

Different controllercan work synchronously when they are started at different times, controlled by the same remote, under same dynamic mode and within 30m distance.



Power Input Brown: V+ Blue: V-
Input Voltage: DC12V~36V
MIBOXER
Waterproof 5-in-1 LED Controller
IP Rate
IP67


Output Mode (LED Wiring)
Mode / Wire | Black | Red | Green | Blue | White | Yellow
Single Color | V+ | W | W | W | W | W
Dual White | V+ | CW | CW | WW | WW |
RGB | V+ | R | G | B | |
RGBW | V+ | R | G | B | W |
RGB+CCT | V+ | R | G | B | CW | WW
Output mode


MiBOXER®
Mi·Light
Subordinate New Brand
Waterproof 5-in-1 LED Controller
Model No.: LS2-WP
Input Voltage: DC12V~36V
Output: 6A/Channel
Total Output Max: 20A
RF: 2.4GHz
Remote Control Distance: 30m
Working Temperature: -20~45°C
Made in China
Power Input
Brown: V+
Blue: V-
IP Rate
IP67
Indicator light color corresponds to the output mode
White Single color mode
Yellow Dual white mode
Red RGB mode
Green RGBW mode
Blue RGB+CCT mode
Short circuit protection
Overcurrent protection
Output Mode (LED Wiring)
Mode / Wire | Black | Red | Green | Blue | White | Yellow
Single Color | V+ | W | W | W | W | W
Dual White | V+ | CW | CW | WW | WW
RGB | V+ | R | G | B
RGBW | V+ | R | G | B | W
RGB+CCT | V+ | R | G | B | CW | WW
2.4GHz
Indicator light
SET
Link / Unlink
(For Remote)

PC plastic shell
strong and durable